



[Click here to see Video](#)

# **ECONOMY COMBINATION L'SEALER AND SHRINK TUNNEL**

**New Design  
Now Featuring  
"Micro Knife"  
Technology**



## **Model PP-1519 ECMC**

This compact Model PP-1519 ECMC L'Sealer with magnetic hold down and power discharge conveyor with attached Tunnel is only 76 inches in total length. Featuring new "Micro Knife" Technology - Will seal PVC or Polyolefin Shrink Films. Tunnel features Live Roller Rod Conveyor with fully Re-Circulating Air Chamber, AC Variable Speed Conveyor, 0 to 60 FPM, Digital Temperature Control and Automatic Cool Down with Shut off. A great machine for low to medium production speeds of 8 to 12 packages per minute. Available in 110 volts or 220 volts.

# Model PP-1519 ECMC Shown with Optional Curved Conveyor



Tunnel Control Panel



Sealer Control Panel



\*This Machine also available without Magnet Hold Down and Power Discharge Conveyor at a Reduced Price

PP 180-24 Gravity Curved Conveyor - Optional



### Tunnel Features

- Fully Re-Circulating Air Chambers
- AC Variable Speed Drive, 0-60 FPM
- Live Roller Rod Conveyor
- Automatic Cool Down with Shut Off
- Digital Temperature Control 0° to 400°
- Anti-Jam Safety Feature on Conveyor



### "Micro Knife" Technology

- Single Piece Teflon Band Ribbon with Round Corner Seal - Reduces Dog Ears
- Will Seal PVC or Polyolefin Shrink Film
- 1 Year Warranty on Band Ribbon
- Dual Magnet Hold Down & Power Discharge Conveyor



### Pin Wheel Hole Punch

- Easy Load Film Rack
- Multiple Pin Wheels Provide Air Evacuation
- Adjustable Product Loading Tray

MODEL	POWER			SHIPPING WEIGHT	SEAL DIMENSIONS		TUNNEL DIMENSIONS			MACHINE DIMENSIONS			MAX. FILM WIDTH	PROD. RATE
	VOLTS	PHASE	AMPS		W	L	L	W	H	L	W	H		
PP-1519ECMC SERIES	110	1	20	460 lbs.	15	19	20	16	6	76	26	50	22	8-12 PPM
	220	1	15											

Solstice Technologies

\* Backed By Preferred Packaging Exclusive 1 Year Warranty

For more information call toll free 1-866-357-4321 or e-mail: <mailto:sales@solstice-inc.com>

Ph: 240-235-0602 Fax: 240-359-4090