



Apollo 7H

Automated 7 drive PC-Connected DVD-R Duplicator with HP FlashJet
4800 Inkjet Printer



*Business Card Compatible

Features

- Up to 600 disc capacity
- Available with 16X Plextor drives.
- Networkable (extra-cost option).
- Direct digital-to-digital copying of Compact Disc and Digital Video Disc over the data bus, "on-the-fly," or cached to hard disk.
- Support for writing to multiple CD-R, or DVD-R devices simultaneously of same image.

Solstice Technologies

For more information call toll free 1-866-357-4321 or e-mail: <mailto:sales@solstice-inc.com>

Ph: 240-235-0602 Fax: 240-359-4090

- Support for the following CD/DVD Duplication tasks:
 - CD/DVD Copy from the same CD/DVD Recorder.
 - Copy CD-ROM/DVD-ROM directly to CD/DVD Recorder.
 - Copy CD-ROM/DVD-ROM to CD/DVD Image file.
 - Copy CD/DVD Image file to CD/DVD Recorder (supports CD/DVD Image files created by CD/DVD Pre-mastering application).
 - Redirection of the output of Easy CD™ or other ASPI compliant CD Pre-mastering application to multiple CD-R/DVD-R drives.
- Low Maintenance.
- Professional Audio Duplication.
- Lower Costs.
- 7 Drives (16x).
- Multiple Simultaneous Duplication.
- Convertible.
- Verification via a low-level compare of source and destination to ensure correct duplicated disks and images.
- Sophisticated audio read resynchronization for unsurpassed reliability in CD
- Digital Audio (CD-DA) duplication of audio CDs for demanding professional applications.
- Disc At Once recording, where possible, for best duplication.
- "On-the-fly" sector cooking with software regeneration or error correction and detection fields and data scrambling.
- Support for most CD-Recorder families as writers.
- An intuitive, easy-to-use interface for both novices and experts.
- Relay mode allows multiple masters and multiple copies to be recorded and printed at the same time.
- Support for transfer of ISRC/UPC, PQ index prints, and R-W sub code information.
- Audio extraction support for .WAV .WMA and .MP3 files.

System Requirements

CPU

AMD AthlonXP, AMD Athlon64, Intel Celeron 1.7GHz or higher, Intel Pentium III 800Mhz or higher, Intel Pentium 4.

Motherboard

Must contain Intel i815, Intel i845, Intel i850, Intel i865, Intel i875, nVIDIA nForce2, or nVIDIA nForce3 chipsets. Examples: AOpen MX3S series, ASUS CUSL2 series, ASUS A7N8X Deluxe.

**NOTE* - Motherboard must have 1 working "Com Port" for Autoloader connection.*

Memory

Minimum of 512 megabytes. should be higher if a large number of drives are in the system. Examples: PC133 SDRAM, PC2100 DDR, PC2700 DDR, PC32000 DDR, PC800 RDRAM.

Solstice Technologies

For more information call toll free 1-866-357-4321 or e-mail: <mailto:sales@solstice-inc.com>

Ph: 240-235-0602 Fax: 240-359-4090

Firewire Host Adapter

Must contain NEC or Texas Instruments chipsets. Examples:
Adaptec, IOI-1394, Maxtor, Orange Micro.

Hard Drive

A fast, non-recalibrating hard disk 7200 RPM or better with 8 MB Cache (avg. access time < 15 msec, transfer rate > 600 KB/second), Big enough for applications and data for Burning DVDs (at least 5 GB free space).

Supported CD formats:

- Audio CD
- Data CD (CD-ROM, Yellow Book Mode 1)
- Data CD (XA format)
- Mixed mode CD (Data + Audio)
- CD-i Bridge format CD (Photo-CD, Video-CD)
- Multisession CD-R and pressed multisession CDs (Enhanced CD, Blue Book)
- Game CDs (many)
- Karaoke and CD+G

SUPPORTED WRITERS

- Plextor DVD-R (16x) CD-R (48x)

Specifications

- Dimensions (WxHxD): 16.5"x24.5"x24.5"
- Weight: 87 lbs/39.7 kg
- Connector: Firewire
- Power Consumption: 115~230 VAC 50~60 Hz

**Solstice Technologies**

For more information call toll free 1-866-357-4321 or e-mail: <mailto:sales@solstice-inc.com>
Ph: 240-235-0602 Fax: 240-359-4090